

# map the internet based on if i get a ping

- [map maker v3.py \(functioning?\) last ping 1.0.212.120 white](#)

# map maker v3.py (functioning?)

## last ping 1.0.212.120 white

```
import os
import socket
import struct
from ping3 import ping
from PIL import Image

print("start running")

def ip_to_int(ip):
    int_ip = struct.unpack("!"I", socket.inet_aton(ip))[0]
    return int_ip
def int_to_ip(i):
    ip = socket.inet_ntoa(struct.pack("!"I", i))
    return ip
def hilbert_curve(n):
    points = [(0, 0)]
    for i in range(n):
        gray = [((k >> i) ^ (k >> (i + 1))) & 1 for k in range(2 ** i)]
        points = _rot(points, gray)
    return points

def _rot(points, gray):
    rot = [(1, 0), (0, 1), (-1, 0), (0, -1)]
    last = points[-1]
    for code in gray:
        last = (last[0] + rot[code][0], last[1] + rot[code][1])
        points.append(last)
    return points

def ping_ip(ip):
    try:
        response_time = ping(ip, timeout=1)
        return 1 if response_time is not None else 0
    except OSError:
        return -1

def main():
    img_size = 65536
    n = 16
```

```
print(f"img size = {img_size}, n={n} Creating a blank image with a white background")
```

```
img = Image.new("1", (img_size, img_size), color="grey")
```

```
pixels = img.load()
```

```
curve_filename = "hilbert_curve v2.txt"
```

```
if os.path.exists(curve_filename):
```

```
    with open(curve_filename, "r") as f:
```

```
        print("reading Hilbert curve coordinates file")
```

```
        curve_points = [tuple(map(int, line.strip().split())) for line in f.readlines()]
```

```
else:
```

```
    print("Generating Hilbert curve coordinates file")
```

```
    curve_points = hilbert_curve(n)
```

```
    with open(curve_filename, "w") as f:
```

```
        for x, y in curve_points:
```

```
            f.write(f"{x} {y}\n")
```

```
ip_range = 2 ** 32
```

```
start_ip_int = 0
```

```
if os.path.exists('ping_status.txt'):
```

```
    with open('ping_status.txt', 'r') as f:
```

```
        lines = f.readlines()
```

```
        if len(lines) > 0:
```

```
            last_line = lines[-1].strip()
```

```
            last_ip, last_result = last_line.split()
```

```
            start_ip_int = ip_to_int(last_ip) + 1
```

```
            print(f"Resuming from IP address {last_ip}, result = {last_result}")
```

```
with open('ping_status.txt', 'a') as f:
```

```
    print("pinging and writing to ping status.txt")
```

```
    for i in range(start_ip_int, ip_range):
```

```
        ip = int_to_ip(i)
```

```
        x, y = curve_points[i % len(curve_points)]
```

```
        result = ping_ip(ip)
```

```
        print(f"result {result} for ip {ip}")
```

```
        if result == -1:
```

```
            f.write(f"{ip} black\n")
```

```
            pixels[x, y] = 0
```

```
        else:
```

```
            pixels[x, y] = result
```

```
            if result == 0:
```

```
                f.write(f"{ip} white\n")
```

```
            else:
```

```
                f.write(f"{ip} black\n")
```

```
        if (i + 1) % (2 ** 24) == 0:
```

```
            img.save("ping_map.png")
```

```
img.save("ping_map.png")
```

```
print("Finished pinging IP addresses and saved final image")
```

```
if __name__ == '__main__':  
    main()
```